



MOSSTYPE

mosstype@mosstype.com

Tel: (201) 444-8000 150 Franklin Turnpike Waldwick, N.J. 07463

Fax: (201) 444-0095

Copying and/or downloading of this information for the purpose of properly utilizing Mosstype Corporation product is allowed provided that (1) the information is copied in full with no changes unless prior agreement is obtained from Mosstype Corporation product, & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

Safety Data Sheet Platekote (7620 0500 06)

page 1 of 4

01/01/2022

Section 1 General Information

Manufacturer
Mosstype Corporation
150 Franklin Turnpike
Waldwick, NJ 07463

Emergency Telephone No.
1-800-255-3924 (Chem-Tel)

Technical & SDS Information
201-444-8000

Preparation Date
09/2020

Product Identification
7620 0500 06

Product Name:
Platekote Release Coating

Section 2 Hazard Identification

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of 1910.1200

GHS Hazard
Symbols



GHS Classification

Gases under pressure – Liquefied Gas
Flammable Aerosol Category 2

Signal Word

Warning

Hazard Statements

Flammable aerosol.
Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Storage

Protect from sunlight. Store in a well-ventilated place.
Do not expose to temperatures exceeding 50 deg. C/ 122 deg. F.

Section 3 Composition/Information on Ingredients

COMPONENT	CAS#	Percent
Halogenated hydrocarbon/ether blend	Mixture	80 – 100

HMIS III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 2 Physical: 1 Personal Protective Equipment: see Section 8

*See www.paint.org/hmis or call the NPCA at 1(202) 462-6272 for more information on this current rating system.

Section 4 First Aid Measures

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion:	Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

Section 5 Fire Fighting Measures

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions.
Fire Fighting Instructions:	Use CO ₂ , foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding areas.

Section 6 Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

Section 7 Handling and Storage

Handling:	Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. May cause frostbite.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use.

Section 8 Exposure Controls/ Personal Protection

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS#</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Halogenated hydrocarbon/ether blend	Mixture	Not established	Not established	1000ppm TWA (Mfr.)

Section 9 Physical and Chemical Properties

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Slight ethereal	Vapor Pressure (PSIG@70 degF):	63.00
Odor Threshold:	Mild	Vapor Density (air =1):	2.01
pH:	No applicable	Relative Density (H2O = 1):	0.81
Melting/Freezing Point (degF):	No data available	Solubility in Water:	Negligible, 0-1%
Boiling Point (deg F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (degF PMCC):	Not applicable	Autoignition Temperature (deg F):	Not applicable
Evaporation Rate:	0.1-0.5(n-Butyl acetate=1)	Decomposition Temperature (deg F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%)	20-40		

Section 10 Stability and Reaction

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition sources such as open flames, sparks, static discharges or flowing metal surfaces. Oxidizers. Acetic acids, Organic acid anhydrides.
Decomposition Products:	This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. When heated to temperatures above 150 deg. C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75ppm.

Section 11 Toxicological Information

Reproductive & Developmental Toxicity:

No data available.

<u>Ingredient</u>	<u>CAS#</u>	<u>Toxicological Data</u>
Halogenated hydrocarbon	Mixture	ORAL ALD Rat > 1500 mg/kg 4HR ALC Rat 383000 ppm
Ether propellant	115-10-6	Inhalation LC50 Rat = 164000 ppm

Section 12 Ecological Information

Ecological Toxicity: No data available
Mobility: No data available

<u>Ingredient</u>	<u>CAS#</u>	<u>Toxicological Data</u>
Ether propellant	115-10-6	48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L

Section 13 Disposal Considerations

Disposal: Dispose according to Federal, State and local regulations.

Section 14 **Transportation Information**

Agency	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable*	2.1	not applicable
IATA	ID8000	Consumer Commodity*	9	not applicable
IMDG	UN1950	Aerosols, Flammable*	2.1	not applicable

*"Limited Quantities" may be applicable for this transportation mode.

Section 15 **Regulatory Information**

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS#	% BY WEIGHT	REGULATORY BODY
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.
No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.
No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

Section 16 **Other Information**

Every reasonable effort has been made to ensure that the safety information on this sheet is accurate. But because Mosstyp has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no expressed or implied warranties of merchantability or fitness for a particular purpose. Mosstyp assumes no liability for injury or incidental or consequential damages arising out of the storage handling, or use of this product.